## Art.-Nr. 12-40801-11

## Waffle Maker Thermocook® incl. Stroopwafel Interchangeable Plates



## **Description**

The Dutch specialty with a caramel syrup core. No optimised interchangeable plate for the Thermor Stroopwafels now turn out just like the Dutch or the waffles as a cup lid for hot beverages: The streeperfect temperature to the waffle and the syr

Multifunction appliance for interchangeable plate (Stroopwafel plates included)

Currently more than 25 different interchangeable available, e.g. for waffles, pizza, crêpes, paninis donuts, sandwiches, churros

Digital timer with large display adjustable up to § An acoustic signal at the end of the cooking time consistent product quality, even with frequently to The acoustic signal reminds the user at the right remove the food so that it does not burn while the performing other tasks at the same time

Optimal heat transfer: Direct contact between he and interchangeable plate due to 8 screws that  $\epsilon$  evenly

New high-performance heating elements with er heating surface for even heat distribution without hotspots Particularly energy-efficient through optimised thermal insulation: A double shielding minimises heat loss and reduces the risk of serious burns

Extremely stable frame construction thanks to reinforced supports

The space of 42 mm between the hot plates and the casing prevents heat accumulation in the appliance and thus extends the service life

Improved ventilation slots ensure heat exchange in the casing Easy cleaning of the accessible surfaces

Particularly service-friendly design for easy maintenance and repair

Front panel with display made of easy-to-clean and durable Autotex polyester

Thermostatic control 0 - 300°C

Pilot light

On/off switch

Stainless steel casing

Height-adjustable feet

Interchangeable plates:

Baking surface 250 x 250 mm

Thickness of the Stroopwaffles approx. 3 mm

Massive cast iron



## I data

ic power: 2,8 kW

je: 230V

y frequency: 50HZ / 60Hz

**x depth x height:** 320 x 340/530 x 275/655 mm

eight: 18 kg

**ng area:** 250 x 250 x ca. 3 mm

