

Art.-Nr. 12-40801DT-12

Thermocook® 120 V Description

Model variant intended for special application scenarios. For 110-120 V supply voltage: Power consumption of 1.7 kW. Please notice that the standard version with 2.8 kW output per interchangeable plate set provides shorter heat-up times, stable temperature operation. Multifunction appliance for international use (included):

Currently more than 25 different interchangeable plates are available, e.g. for waffles, pizzas, donuts, sandwiches, churros

Digital timer with large display

An acoustic signal at the end of the cooking cycle ensures consistent product quality, even at high temperatures

The acoustic signal reminds you to remove the food so that it does not burn and you can perform other tasks at the same time

Optimal heat transfer: Direct contact between the heating plate and interchangeable plate ensures even heating

New high-performance heating plate with a large heating surface for even heating

Particularly energy-efficient thermal insulation: A double shielding reduces the risk of serious burns

Extremely stable frame construction thanks to reinforced supports

The space of 42 mm between the hot plates and the casing prevents heat accumulation in the appliance and thus extends the service life

Improved ventilation slots ensure heat exchange in the casing

Easy cleaning of the accessible surfaces

Particularly service-friendly design for easy maintenance and repair

Front panel with display made of easy-to-clean and durable Autotex polyester

Thermostatic control 0 - 300°C

Pilot light • On/off switch

Stainless steel casing

Height-adjustable feet

Incl. power cord US (Type B). Not compatible with 230 V power cords

Neumärker® Technical data



Electric power: 1,7 kW



120V

60Hz

320 x 340/350 x 275/655 mm

9 kg

