

Art.-Nr. 12-40801DT-AU

Description

Thermocook® 2,2 kW

Model variant intended for special application scenarios.

Optimized for 220-230 V circuits protected by 10 A breakers:

Power consumption of 2.2 kW.

Please notice that the standard version with 2.8 kW output per interchangeable plate set provide the best conditions for short heat-up times, stable temperature operation.

Multifunction appliance for international use (included)

Currently more than 25 different interchangeable plates are available, e.g. for waffles, pizzas, donuts, sandwiches, churros etc.

Digital timer with large display

An acoustic signal at the end of the cooking cycle ensures consistent product quality, even at high temperatures.

The acoustic signal reminds you to remove the food so that it does not burn. You can also perform other tasks at the same time.

Optimal heat transfer: Direct contact between the heating surface and interchangeable plate due to the pressure applied evenly.

New high-performance heating surface for even heating and long service life.

Particularly energy-efficient thanks to excellent insulation: A double shielding reduces the risk of serious burns.

Extremely stable frame construction thanks to reinforced supports.

The space of 42 mm between the hot plates and the casing prevents heat accumulation in the appliance and thus extends the service life.

Improved ventilation slots ensure heat exchange in the casing.

Easy cleaning of the accessible surfaces.

Particularly service-friendly design for easy maintenance and repair.

Front panel with display made of easy-to-clean and durable Autotex polyester.

Thermostatic control 0 - 300°C

Pilot light

On/off switch

Stainless steel casing

Height-adjustable feet

Incl. power cord Schuko (Type E/F)

Technical data

Neumärker®



Electric power: 2,2 kW



Voltage: 230V

50Hz / 60Hz

320 x 340/530 x 275/655 mm

9 kg

