



Description

Multifunction appliance for i
included)

Currently more than 25 diffe
available, e.g. for waffles,&r
sandwiches, churros

Digital timer with large display adjustable up to 9:59 min/sec

An acoustic signal at the end of the cooking time ensures
consistent product quality, even with frequently changing staff
The acoustic signal reminds the user at the right time to
remove the food so that it does not burn while they are
performing other tasks at the same time

Optimal heat transfer: Direct contact between heating element
and interchangeable plate due to 8 screws that are tightened
evenly

New high-performance heating elements with enlarged
heating surface for even heat distribution without hotspots

Particularly energy-efficient through optimised thermal
insulation: A double shielding minimises heat loss and
reduces the risk of serious burns

Extremely stable frame construction thanks to reinforced
supports

The space of 42 mm between the hot plates and the casing
prevents heat accumulation in the appliance and thus extends
the service life

Improved ventilation slots ensure heat exchange in the casing

Easy cleaning of the accessible surfaces

Particularly service-friendly design for easy maintenance and
repair

Front panel with display made of easy-to-clean and durable
Autotex polyester

Thermostatic control 0 - 300°C

Pilot light

On/off switch

Stainless steel casing

Height-adjustable feet

Thermocook Twin is not suitable for the following

interchangeable plates: Pizza, Crêpes, Waffles on a stick

5,6 kW

400V



Supply frequency:

50Hz / 60Hz



Gas power:

'0'



Width x depth x height:

610 x 340/530 x 275/655 mm



Net-weight:

18 kg



Number of waffles:

'0'